



ATA KİMYA
İNŞAAT SANAYİ ve TİC. LTD. ŞTİ.

Peramin® DEFOAM 50-51PE

Defoaming agent

Description

The defoaming agent **Peramin® DEFOAM 50-51PE** is a powder product based on a mixture of hydrophobic esters.

Compatibility

Peramin® DEFOAM 50-51PE is compatible with all admixtures on the market and especially with **Peramin® CONPAC & SMF**, but laboratory trials are advised before any industrial use.

The defoaming agent **Peramin® DEFOAM 50- 51PE** is recommended for powder formulations. Before use, it is recommended to read the material safety data sheet.

Application

Dry-mortar industry

Concrete

Specifications

Appearance: White powder
Bulk Density (kg/m³): 450 - 650
Granulometry: < 600 µm

Dosage

The defoaming agent **Peramin® DEFOAM 50-51PE** can be used in dry mixes, which will be diluted in water. The fineness of its particles improves the flow of powder formulations and reduces risk of lumps. Typically, the dosage of **Peramin® DEFOAM 50-51PE** varies from 0.05 to 0.5% weight / weight to binder..

Packaging and storage

Big-bag of 450 kg
Sack of 25 kg

Conditions of storage

Shelf life : 12 months at 5 – 25°C
Store in cool, dry area.